

CIRCULAR LED HIGH BAY LIGHTS











The Circular High Bay Light from InnovateLighting is the energy-efficient solution to achieving clean and professional lighting in any industrial setting.

Adopting the latest LED lighting technology, with longer lifespan, lower maintenance cost and higher efficiency – this versatile product is ideal for areas with a mounting height of 5 metres or above. Popular applications include warehouses, factories, exhibition halls and showrooms.

Features:

- Highly configurable 'built to order' products
- Nichia LED chip and integrated Meanwell driver
- Highly energy efficient 130 lm/w
- Series wattage range 100W 300W
- Lumen packages 13,000lm 40,500lm
- Compact, low weight and pure aluminium heat sink for maximum heat dissipation
- Waterproof rating of IP65 making it suitable for outdoor use
- Long-lasting LED lifespan of more than 50,000 hours
- 5-year warranty as standard

Configure:

To ensure that our products meet your exact application, we offer highly-customisable solutions. First confirm your lumen requirement, and then configure your fixture based on the following options:

- 1. Installation: Ceiling or Wall-Mounted?
- 2. Beam Angle: 30°, 60°, 90° or 120°?
- 3. Intelligent Control Options: Dimmable, Motion-Sensor or Zigbee?

TECHNICAL SPECIFICATIONS

Lumens	13,000lm	15,600lm	19,500lm	26,000lm	32,400lm	40,500lm
Wattage	100W	120W	150W	200W	240W	300W
HID/HPS/MH Equivalent	250W	300W	375W	500W	600W	750W
System Efficiency	130 lm/w	130 lm/w	130 lm/w	130 lm/w	135 lm/w	135 lm/w
Fixture Size	φ388×195.5mm	φ388×195.5mm	φ388×195.5mm	φ388×206.5mm	φ388×207mm	φ388×257.5mm
Fixture Weight	6.1kg	6.4kg	6.4kg	7.2kg	7.2kg	8.1kg
LED Chip	Nichia					
Integrated LED Driver	Meanwell					
Colour Temp	5000K Daylight White					
Colour Rendering Index	Ra70					
Mains Power	AC 100 ~ 240V, 50/60 Hz					
Fixture Material	Aluminium					
Fixture Colour	Black					
Lens Material	Polycarbonate					
Waterproof Protection	IP65 Rated					
Working Temperature	-30°C ~ +50°C					
Working Humidity	15% ~ 90%					
LED Lifespan	> 50,000 Hours (TA 30°C @ L70)					
Installation Options	Ceiling or Wall Mounted					
Beam Angle Options	30°, 60°, 90°, 120°					
Control Options	Dimmable, Motion Sensor, ZigBee					
Certifications	CE, RoHS, IP65					
Warranty	5-Years					

