



InnovateLighting's specialist linear LED high bays have been designed to be a powerful directed light solution that can accurately illuminate the aisles and racking areas of industrial warehousing facilities.

Our range is highly efficient, easy to install and produces an excellent quality of light. Suitable for areas with a mounting height of 5 meters up to 30 meters. Popular applications include warehouses, factories, exhibition halls and showrooms.

Features:

- Highly configurable 'built to order' products
- Nichia LED chip and integrated Meanwell driver
- Highly energy efficient 125 lm/w
- Series wattage range 60W - 180W
- Lumen packages 7,500lm - 22,500lm
- Extruded pure aluminium housing ensures superb heat dissipation
- Waterproof rating of IP65 making it suitable for outdoor use
- Long-lasting LED lifespan of more than 50,000 hours
- 5-year warranty as standard

Configure:

To ensure that our products meet your exact application, we offer highly-customisable solutions. First confirm your lumen requirement, and then configure your fixture based on the following options:

1. Installation: Cable-Hanging or Fixed-Bracket Ceiling Mount?
2. Beam Angle: 30°x70°, 60°x90°, 40°x130°, 90° or 120°?
3. Intelligent Control Options: Dimmable, Motion-Sensor or Zigbee?

TECHNICAL SPECIFICATIONS

Lumens	7,500lm	11,250lm	15,000lm	18,750lm	22,500lm
Wattage	60W	90W	120W	150W	180W
HID/HPS/MH Equivalent	150W	225W	300W	375W	400W
System Efficiency	125 lm/w	125 lm/w	125 lm/w	125 lm/w	125 lm/w
Fixture Size	486×137×102mm	718×137×102mm	948×137×102mm	1178×137×102mm	718×275×102mm
Fixture Weight	3.4kg	4.7kg	5.7kg	6.9kg	8.5kg
LED Chip	Nichia				
Integrated LED Driver	Meanwell				
Colour Temp	5000K Daylight White				
Colour Rendering Index	Ra70				
Mains Power	AC 100 ~ 240V, 50/60 Hz				
Fixture Material	Aluminium				
Fixture Colour	Black				
Lens Material	Polycarbonate				
Waterproof Protection	IP65 Rated				
Working Temperature	-30°C ~ +50°C				
Working Humidity	15% ~ 90%				
LED Lifespan	> 50,000 Hours (TA 30°C @ L70)				
Installation Options	Cable-Hanging or Fixed-Bracket Ceiling Mount				
Beam Angle Options	30°x70°, 60°x90°, 40°x130°, 90°, 120°				
Control Options	Dimmable, Motion Sensor, ZigBee				
Certifications	CE, RoHS, IP65				
Warranty	5-Years				